

Technical Data Sheet

LANKO

ROCKFIL



How to use

Substrate Preparation

Remove oil, dust or traces of foreign materials before application of Lanko Rockfil.

Mixing

Hand mixing: Add 1kg of Lanko Rockfil to 460ml water. Mix thoroughly and break lumps with spatula until mixture is smooth in texture and has good consistency.

Electric Mixer: Mix approximately 9.2 liters of water with 20kg of Lanko Rockfil and mix thoroughly for 3 - 5 minutes until desired homogeneous paste is achieved.

Application

- Fill-in open space between panels with Lanko Rockfil using a joint knife.
- Place the joint tape or mesh tape over the product.
- Lightly smoothen the tape into the product using a putty knife or trowel.
- Apply a thin coat over the joint to prevent the edge from wrinkling.
- Allow the product to dry for 20 - 30 minutes.
- Apply final coat with putty knife or trowel.
- Allow product to dry completely.
- Product can be sanded to smoothen surface.
- Store and cover unused Lanko Rockfil in a plastic container for later application.
- Paintable after 24 hours (depending on actual site conditions)

Cleaning

- Use water to clean up excess Lanko Rockfil and tools with clean water.

Precautions

- Non hazardous.
- Avoid contact with skin or swallowing of product
- In case of eye contact, wash with plenty of water.
- If irritation persists, seek immediate medical attention

Shelf life & Storage:

Store in a cool dry place. If properly stored in its original, unopened container, product life is 6 months.

PREMIUM GRADE JOINT & INTERNAL SKIMMING COMPOUND



pg2

RENDERING

PAREXGROUP INC.

No. 888 Cayetano Avenue, Warehouse 5 & 6, C-5 Extension, Diversion Road,
Brgy. Palamong-Tipas, Taguig City 1637
Telephone : 672-1705 and 790-9800; Fax Number : (632)790-9828
Web: www.parexgroup.com.ph

Technical Data Sheet

LANKO

ROCKFIL



Description

Lanko Rockfil powder is a cement-free, polymer-based, joint and internal skimming compound.

Lanko Rockfil only requires addition of water on site to give a smooth and homogeneous paste when mixed by hand or electric mixer.

Uses

- It is ideal for smoothening and finishing plaster board joints and walls prior to painting.
- Suitable for use on gypsum boards, cement boards, masonry and textured wall boards. Lanko Rockfil is fitted for indoor use only.

Advantages

- Environment-friendly (VOC free formulation)
- Quick-drying when applied
- Gives a hard surface which can be sanded if needed (can be feather edged)
- Can be used for both paper tape and mesh tape
- Long pot life, excess LANKO Rockfil can be stored in properly sealed containers (which can be used within 24 hours) thereby minimizing product wastage.

Product Use Technical Data

Appearance:	Off-white powder
Water/Powder Ratio:	0.46 - 0.47
Specific Gravity:	1.6±0.05
Pull-out Strength: (on gypsum board)	0.3N/mm ²
Pot life:	1-2 hours (depending on actual site conditions)
Coverage:	20 kg of powdered Lanko Rockfil can cover approximately 7.5 to 8.5m ² at 1.0mm thickness.
Packaging:	20 Kg bag

**PREMIUM GRADE
JOINT & INTERNAL
SKIMMING COMPOUND**



RENDERING

pg 1

DISCLAIMER

The use of these products is beyond the manufacturer's control and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Specifications are subject to change without prior notice.